



Creaturelab Network Solution

RC-1004

Industrial 4G / 3G Router



RC-1004 is an industrial-grade high-speed wireless router based on GPRS/CDMA/WCDMA/EVDO/LTE cellular mobile network to provide users with high-speed wireless Internet and wireless data transmission functions.

This product adopts industrial-grade dedicated communication 32-bit RISC processors, industrial-strength wireless mold piece, the LINUX embedded real-time operating system, support a SIM card interface, four LAN, a WAN port, a USB interface and WIFI interface, at the same time provide LAN port equipment or WIFI Internet or data transmission function.

It also adopts wide temperature, wide voltage input and EMC test with electromagnetic compatibility. Has been widely used in the Internet of things industry chain of M2M industry, such as self-service terminals, smart grid, smart transportation, smart home, financial, mobile POS terminals, supply chain automation, industrial automation, intelligent buildings, fire control, public security, environmental protection, meteorology, digital medical treatment, telemetry, military, space exploration, agriculture, forestry, water, coal, petrochemical and other fields

Feature

- ✓ LTE Band Support
 - EU Model: 2100/1800/2600/900/800 MHz (B1/B3/B7/B8/B20)
 - US Model: 1900/AWS/850/700/700/1900 MHz (B2/B4/B5/B13/B17/B25)
- ✓ Built-in high speed 4-port Ethernet switch,4x LAN port
- ✓ 1X WAN port
- ✓ Power input supported DC5-30VDC
- ✓ The power and the antenna with lightning protection
- ✓ Support VPN client (PPTP, L2TP, OPENVPN, IPSEC and GRE) (only for VPN version)
- ✓ Support hardware and software WDT



02-433-4333

/vizertech

@vizer

/vizertech

บริษัท ครีเอทีฟแล็บ เน็ตเวิร์ค โซลูชั่นส์ จำกัด
357 ถนนรัชดาภิเษก แขวงบางนาพรุ เขตบางพลัด กรุงเทพฯ 10700
Email : info@creaturelab.co.th web : www.creaturelab.co.th

Cellular Interface		
Band Supported	4G/3G/2G Version	<ul style="list-style-type: none"> • FDD:B1/ B2①/ B3/ B4/ B5/ B7/ B8/ B28, 3G:B1/ B2/ B5/ B8 • Supported WCDMA/HSDPA/HSPA+ B1/ B2/ B5/ B8 • Supported CDMA 1X/EVDO BC0 • Supported GSM/GPRS/EDGE B2/ B3/ B5/ B8
	EVDO 3G Version	Supported EVDO, CDMA2000 1X
	HSDPA 3G Version	Supported HSUPA/HSDPA/UMTS/EDGE/GPRS/GSM
Theory of Bandwidth	<ul style="list-style-type: none"> • LTE CAT4- DL :50Mbps, UL :150Mbps • TD-HSDPA/HSUPA-DL : 2.2 Mbps, UL : 2.8 Mbps • HSPA+-DL : 5.76 Mbps, UL : 4.2 Mbps • WCDMA – DL/UL : 384Kbps • CDMA2000/EVDO DL : 1.8 Mbps, UL : 3.1 Mbps 	
WiFi supported		
Standards	Supported IEEE 802.11 b/g/n	
Frequency	2.4GHz (ISM band supported)	
WiFi Rate	300Mbps	
Security	64/128-bit WEP (Wired Equivalent Privacy)	
	WPA & WPA-PSK & WPA2 -PSK (Wi-Fi Protected Access)	
Router characteristics		
Firewall	Network Address Translation (NAT)	
Frequency	State full Packet Inspection (SPI)	
Media Access Control	VPN protocol	
VPN protocol	Supported IPSec, PPTP,L2TP	
DHCP	Build-in DHCP (Dynamic Host Configuration Protocol)	
Others protocol	Supported PPP,PPOE, DDNS,ICMP,VRRP etc	
Hardware		
CPU	32-bit high performance communication CPU	
Flash/RAM	16M/128M	
OS	LINUX latest version	
Interface		
LAN	4 x 10/100M port	
WAN	1x 10/100M WAN port	
USB	1x USB2.0 port	
SD Card	1x SD port	
Debug	1x Debug interface (RS232 -RJ45 connector)	
Reset	1x Reset	
Antennas	1x 3G/4G Antenna(50Ω SMA interface)	
	2x WiFi or GPS antenna (option) , or can use for 4G MIMO antenna	
LED	Power-SYS-LAN-WiFi-3G/4G LED	
SIM slot	Supported 1.8/3.3V SIM card we support SIM card converter meet all size sim card	
Power		
Default power	DC 12V/1A power adapter (US,EU etc stander option)	
Input VDC	5~38V	
Power Dissipation	Min: 260mA@12VDC MAX: 500mA@12VDC Average:320mA@12VDC	
Physical property		
Operating Temperature	Storage Temperature: (-30°C to 70°C)	
	Operating Temperature: (-20°C to 65°C)	
Relative Humidity	95%	
Size	L*S*H: 173mm x100mm x 25mm	
Weight	Net weight:600g	
	Packing weight: 1.5kg	
Other		
Warranty	5 years	
Package contains	CNS Router,1.5m long RJ45 Cable,12V/1A Power Adapter,Antennas User manual (Option choose PDF) ,Warranty card, CERTIFICATION	